



SPECIFICATIONS 仕様			
PISTON DIA ピストン径		138	mm
PISTON STROKE ピストンストローク		19	mm
PISTON THRUST ピストン推力	押 PUSH	21.9	kN
	引 PULL	20.0	kN
			For B-206 B-208
			(Oil pressure 2.1 MPa)
PISTON THRUST ピストン推力	押 PUSH	38.0	kN
	引 PULL	34.8	kN
			For B-208 B-208R
			(Oil pressure 3.4 MPa)
PISTON THRUST ピストン推力	押 PUSH	47.0	kN
	引 PULL	43.0	kN
			For B-210 B-210R
			(Oil pressure 4.12 MPa)
PISTON THRUST ピストン推力	押 PUSH	47.9	kN
	引 PULL	43.9	kN
			(Oil pressure 4.2 MPa)
MAX. OPERATING PRESSURE 最大作動圧力		4.2	MPa
MAX. SPEED 最大速度		6000	min ⁻¹
MASS 質量		14.8	kg
MOMENT OF INERTIA 慣性モーメント		0.043	kg·m ²
OIL LEAKAGE 漏油量		3.9	ℓ/min
			(ISO VG 32, 50°C, 3.0MPa)

- Accessory
付属品
- 六角穴付ボルト M8x70 : 6ヶ
Hex. socket head cap screw M8x70 : 6 pcs
 - ホースニップル φ33 : 2ヶ
Hose nipple φ33 : 2 piece
 - 六角穴付ボルト M5x8 : 2ヶ
Hex. socket head cap screw M5x8 : 2 pcs

バルーフ リニアセンサ仕様 BALLUFF LINEAR SENSER SPECIFICATIONS	
型式 Type	BIP AD2-T030-02-S4
出力電圧 Output voltage	0~10 V
検出範囲 Working range	0~30 mm
繰返し性能 Repeat accuracy	±100μm
保存周囲温度 Ambient temperature	-25~85°C

6-M8 mounting bolt
6-M8取り付けボルト
(60°等配)
(60°equal-spaced)

View of C
C矢視図
(S=1/3)

CAREER			SCALE	TYPE	SR1453CBIP	WEIGHT	kg
MANAGER	CHIEF	DRAWN BY	4:5	NAME	SR1453CBIP	ROTARY HYDRAULIC CYLINDER	
Kitagawa Corporation			DATE	NAME	SR1453CBIP	ガイワイ	
				DRW NO.	61R278408	OUTSIDE VIEW	